



## MCP 6001 Customer Configuration Sheet

Please fill in all of the appropriate information. Your order is not valid and will not be processed unless all of the shaded sections are complete. Check the box next to the desired input option and the desired output option. Complete a separate Configuration Sheet for each different configuration you are ordering.

### Single/Dual Voltage Output Models with Isolation Transformer

PART #	STANDARD FEATURES	DIMENSIONS (HXWXD)	NET WT / SHIP WT
90000334	Input-Hardwire Output-Hardwire	31.9 X 10.2 X 21.8 (inches)	309 / 344 (lbs)

OPTIONS		COST	CHECK
INPUT	208 Volts	N/C	
INPUT	240 Volts	N/C	
OUTPUT	120 Volts	N/C	
OUTPUT	120 Volts / 120 Volts	N/C	
OUTPUT	208 Volts	N/C	
OUTPUT	120 Volts / 208 Volts	N/C	
OUTPUT	240 Volts	N/C	
OUTPUT	120 Volts / 240 Volts	N/C	

1. Is there a delivery dock and/or a forklift at this location? YES  NO   
**\*If NO, the unit will need to be delivered in a lift gate truck.**

2. Is inside delivery required at this location? YES  NO

3. Is the unit to be delivered in a multi-storied building? YES  NO   
**\*If YES:**

a). On which floor is the unit to be delivered? \_\_\_\_\_

b). Is a freight elevator available to make the delivery? YES  NO

4. Is a delivery appointment required? YES  NO   
**\*If YES, please provide the contact information below:**

Contact \_\_\_\_\_ Phone# \_\_\_\_\_

**\*Additional freight charges will apply.**

If you have any other, delivery requirements please notify your MINUTEMAN sales representative.

Company Name:	Fax Number:
Contact Name:	Phone Number:
Option Numbers:	
Date:	Signature:

MINUTEMAN UPS / Para Systems, Inc.  
 1455 LeMay Drive, Carrollton, TX 75007  
 Toll-free: 800-238-7272 Phone: 972-446-7363 FAX: 972-446-9011  
 Internet: www.minutemanups.com www.sizemyups.com